

Quick Reference Guide for TADPOLE CONTROL SYSTEM



INITIAL START-UP

When you power up the spa, it will begin the Priming mode. The Priming mode will last for up to 4 minutes. To exit Priming mode early press TEMP.

SPA MODES

1. Press TEMP followed by LIGHT to enter mode programming.
2. Press TEMP to cycle through the desired mode.
3. Press LIGHT to confirm selection.

This multi-button sequence allows you to switch between the following modes:

- **Standard:** maintains desired temperature.
- **Economy:** heats spa to set temperature only during filter cycles.
- **Sleep:** heats spa to within 20°F of set temperature only during filter cycles.

STANDBY MODE

Standby mode prevents spa from turning on while changing filter cartridge or JetPaks™.

1. Press TEMP.
2. Press AUX.
3. Press any button to exit.

TEMPERATURE

To increase or decrease the set temperature:

1. Press TEMP once to display the set temperature.
2. Continue pressing TEMP to increase or decrease the temperature.

Note: To reverse direction, pause 3-5 seconds in between pressing TEMP.

ADJUSTING FILTER CYCLES

The factory preset filter cycle is every 2 hours.

1. Press TEMP then JETS 1.
2. Press TEMP to select the filter duration.
Press JETS 1 to select the number of filter cycles.
3. Press TEMP to modify.
4. Press TEMP to modify.
5. Press JETS 1 to exit program.

JETS 1

Pump 1 high-speed will turn off automatically after 15 minutes and low-speed will turn off automatically after 2 hours.

1. Press JETS 1 to turn on pump 1.
2. Press JETS 1 to shift between low and high speeds.
3. Press JETS 1 again to turn off jets.

Note: Jets 1 will not turn off if the spa is in filtration mode or heating.

LIGHT

Press LIGHT to turn light on and off. The light will turn off automatically after 4 hours.

LED LIGHT (optional)

The light will turn off automatically after 4 hours.

1. Press LIGHT to turn on light.
2. Press LIGHT again to shift through color options.

Note: Only pause 2-3 seconds in between color selection.

REMINDERS

To dismiss maintenance reminders, press TEMP and then LIGHT.

Quick Reference Guide for SELECT CONTROL SYSTEM



INITIAL START-UP

When you power up the spa, it will begin the Priming mode. The Priming mode will last for up to 4 minutes. To exit Priming mode early press TEMP.

SPA MODES

1. Press TEMP followed by LIGHT to enter mode programming.
2. Press TEMP to cycle through to desired mode.
3. Press LIGHT to confirm selection.

This multi-button sequence allows you to switch between the following modes:

- **Standard:** maintains desired temperature.
- **Economy:** heats spa to set temperature only during filter cycles.
- **Sleep:** heats spa to within 20°F of set temperature only during filter cycles.

STANDBY MODE

Prevents spa from turning on cartridge or JetPaks™.

1. Press TEMP.
2. Press AUX.
3. Press any button to exit.

TEMPERATURE

To increase or decrease the set temperature:

1. Press TEMP once to display the set temperature.
2. Continue pressing TEMP to increase or decrease the temperature.

Note: To reverse direction, pause 3-5 seconds in between pressing TEMP.

ADJUSTING FILTER CYCLES

The factory preset filter cycle is every 2 hours.

1. Press TEMP then JETS 1.
2. Press TEMP to select the filter duration.
3. Press JETS 1 to select the number of filter cycles.
4. Press TEMP to modify.
5. Press JETS 1 to exit program.

JETS 1

Pump 1 high-speed will turn off automatically after 15 minutes and low-speed will turn off automatically after 2 hours.

1. Press JETS 1 to turn on pump 1.
2. Press JETS 1 to shift between low and high speeds.
3. Press JETS 1 again to turn off jets.

Note: Jets 1 will not turn off if the spa is in filtration mode or heating.

JETS 2 (optional)

Pump 2 will turn off automatically after 15 minutes.

1. Press JETS 2 to turn on pump 2.
2. Press JETS 2 to shift between low and high speeds.
3. Press JETS 2 again to turn off jets.

Note: An optional auxiliary control button on the side of the spa can activate either pump.

LIGHT

Press LIGHT to turn light on and off. The light will turn off automatically after 4 hours.

LED LIGHT (optional)

The light will turn off automatically after 4 hours.


1. Press LIGHT to turn on light.
2. Press LIGHT again to shift through color options.

Note: Only pause 2-3 seconds in between color selection.

REMINDERS

To dismiss maintenance reminders, press TEMP and then LIGHT.

Quick Reference Guide for PREMIER CONTROL SYSTEM



INITIAL START-UP

When you power up the spa, it will begin the Priming mode. The Priming mode will last for up to 4 minutes. To exit Priming mode early press WARMER or COOLER.

SPA MODES

1. Press MODE/PROG to enter mode programming.
2. Press COOLER to cycle through modes.
3. Press MODE/PROG to confirm.

This multi-button sequence allows you to switch between the following modes:

- **Standard:** maintains desired temperature.
- **Economy:** heats spa to set temperature only during filter cycles.
- **Sleep:** heats spa to within 20°F of set temperature only during filter cycles.

STANDBY MODE

Prevents spa from turning on while changing filter cartridge or JetPaks™.

1. Press WARMER.
2. Press JETS 2 or AUX.
3. Press any button to exit.

ADJUSTING FILTER CYCLES

Please refer to the Premier Control system section in the Owner's Manual.

TEMPERATURE

To increase or decrease the set temperature:

1. Press WARMER or COOLER button once to display the set temperature.
2. Press WARMER or COOLER to increase or decrease the temperature.

INVERT DISPLAY

To change the direction of the numbers displayed on the control pad, press WARMER or COOLER followed by the OPTION button.

JETS 1

Pump 1 high-speed will turn off automatically after 30 minutes and low-speed will turn off automatically after 4 hours.

1. Press JETS 1 to turn on pump 1.
2. Press JETS 1 to shift between low and high speeds.
3. Press JETS 1 again to turn off jets.

Note: Jets 1 will not turn off if the spa is in filtration mode or heating.

JETS 2 (optional)

Pump 2 will turn off automatically after 30 minutes.

1. Press JETS 2 once to turn on pump 2.
2. Press JETS 2 to shift between low and high speeds.
3. Press JETS 2 again to turn off jets.

Note: An optional auxiliary control button on the side of the spa can activate either pump.

LIGHT

Press LIGHT to turn the light on and off. The light will turn off automatically after 4 hours.

LED LIGHT (optional)

The light will turn off automatically after 4 hours.

1. Press LIGHT to turn on light.
2. Press LIGHT again to shift through color options.

Note: Only pause 2-3 seconds in between color selection.

TIME

To set or change the time:

1. Press TIME then MODE/PROG.
2. Press either WARMER or COOLER to adjust hour.
3. Press MODE/PROG to switch to minutes.
4. Press TIME to confirm.

REMINDERS

To dismiss maintenance reminders, press TEMP and then LIGHT.